



# CENTAURI

**CENTAURI** is the most advanced and efficient Luminaire for Industrial, Retail or Transportation Applications where uniform lighting is required without shadowing or obfuscation occurring

Is ideal for Production lines, Supermarkets or Metro Stations, amongst others.

Centaury is available in indoor IP40 & also outdoor IP65 versions both supplied with high impact protection IK09 and 3 sizes. It can be installed directly in ceiling or hanging from 4m to 10m or more



Models	power	lumen output (lm)	size (mm)	weight (kg)
LC-CENT22	22W	2.860	600x33x68	3
LC-CENT44	44W	5.720	1200x33x68	3.5
LC-CENT54	54W	7.020	1500x33x68	4
LC-CENT80	80W	10.400	1500x33x68	4.5

\*other configurations can be customized

## Waterproof IP65



for indoor & outdoor rough environments, centauri is available in IP65 waterproof protection grade

## Specifications


input	230V~50Hz
power factor	> 90 %
CRI	> 70
CCT	3000K to 6500K
body	aluminum
efficiency (real)	> 130lm/W
lifespan	> 100.000h
ingress protection	IP40 / IP65
impact protection	IK09
working temp.	-20°C to +50°C
installation	surface ceiling or suspended
mounting height	from 3m to 10m

## Dimming


optional dimming control for light output is available for standard protocols 0-10V, DALI and PWM

## Optic Modules


To comply with the most demanding lighting scenarios photometrics are available from a wide range of beam angles - the independent optic modules are specially designed with individual lenses for each LED with optional angles of 20°, 30°, 60° and 90° (waterproof)




narrow 30° for high-bay



60° for offices or supermarkets



90° for offices or supermarkets



narrow double asymmetric 25°

**OSRAM**  
LED Technology included

## Factory

Lux Concept  
Zona Industrial Parkamado Pav 6 3800-055 Aveiro  
Portugal

[www.luxconcept.pt](http://www.luxconcept.pt)

## Contact us

+351 234 420 010  
[info@luxconcept.pt](mailto:info@luxconcept.pt)